



printhead cleaner *built in* your ribbon.

- Built right into your thermal transfer ribbons
- Preventative maintenance
- Fast and easy to use
- Maintains excellent print quality
- Prolongs printhead life
- Minimizes costly downtime



## PREMIUM RESIN

### Technical Specifications

Color Code Tab..... Blue  
 Maximum Print Speed ..... 6 IPS  
 Film Thickness..... 4.5 Microns  
 Total Ribbon Thickness..... 6.2 Microns  
 Transmission Density ..... 1.00  
 MacBeth Scale  
 Ink Melting Point..... 110°C/230°F

UL and CSA Labeling Reference:  
 Avery Fassion: UL MH17205, CSA 97198  
 FLEXcon: UL MH16635, CSA 99214  
 3M: UL MH16411



### Super Premium Resin

The ultimate in durability

#### Benefits

- Maximum durability for harsh environment labeling
- Highest level of resistance to abrasion, heat, steam and various chemicals
- Prints exceptionally on high end films including polyester, vinyl and polyamide

#### Recommended Stock

Polyester films  
 Vinyl  
 Polyamide films



What you need to know to quote ribbon business.

### Thermal Transfer Ribbon

#### STORAGE CONDITIONS

For optimal print results, thermal transfer printing should occur in the temperature range of 41° F to 95° F at 45% to 85% relative humidity. Suggested storage conditions for up to one year duration are 23° F to 104° F at 20% to 85% relative humidity. Exposing thermal transfer ribbons to direct sunlight or moisture will cause damage to the ribbons.



Ph: (800) 700-7377  
 Ph: (949) 888-3880  
 Fax: (949) 888-3883

**ACCURATE IMAGING RESOURCES**  
 22532 Avenida Empresa  
 Rancho Santa Margarita, CA 92688