



printhead cleaner built in your ribbon.

- Built right into your thermal transfer ribbons
- Preventative maintenance
- Fast and easy to use
- Maintains excellent print quality
- Prolongs printhead life
- Minimizes costly downtime



PREMIUM WAX RESIN

Technical Specifications

Color Code Tab.....	Teal
Maximum Print Speed	8 IPS
Film Thickness.....	4.5 Microns
Total Ribbon Thickness.....	8.4 Microns
Transmission Density	2.6
	MacBeth
	Scale
Ink Melting Point.....	65°C/149°F



Premium Wax/Resin

Outstanding Versatility and Print Quality

Benefits

- Perform on a broad range of premium applications
- Prints on wide range of substrates including coated papers and smooth synthetic films.
- Excellent durability
- Stands up to rough handling, abrasion or moderate solvents
- Specially formulated backcoat protects the printhead

Recommended Stock

Coated paper (matte, semi gloss, high gloss)	Polypropylene
Polyolefin	Polyethylene
Polyester	



What you need to know to quote ribbon business.

Thermal Transfer Ribbon

STORAGE CONDITIONS

For optimal print results, thermal transfer printing should occur in the temperature range of 41° F to 95° F at 45% to 85% relative humidity. Suggested storage conditions for up to one year duration are 23° F to 104° F at 20% to 85% relative humidity. Exposing thermal transfer ribbons to direct sunlight or moisture will cause damage to the ribbons.



Ph: (800) 700-7377
Ph: (949) 888-3880
Fax: (949) 888-3883

ACCURATE IMAGING RESOURCES
22532 Avenida Empresa
Rancho Santa Margarita, CA 92688