



printhead cleaner *built in your ribbon.*

- Built right into your thermal transfer ribbons
- Preventative maintenance
- Fast and easy to use
- Maintains excellent print quality
- Prolongs printhead life
- Minimizes costly downtime



SPECIALTY WAX+

Technical Specifications

Color Code Tab.....	Purple
Maximum Print Speed	12 IPS
Film Thickness.....	4.5 Microns
Total Ribbon Thickness.....	7.5 Microns
Transmission Density	1.45
	MacBeth
	Scale
Ink Melting Point.....	62°C/144°F



General Purpose Wax

Added Durability

Benefits

- Prints at low heat settings
- Specially formulated backcoat protects the printhead
- Outstanding print performance on coated stocks
- Offers higher durability than most waxes on coated stocks

Recommended Stock

Coated paper tag and label stocks
Polyethylene films
Polypropylene films



What you need to know to quote ribbon business.

Thermal Transfer Ribbon STORAGE CONDITIONS
For optimal print results, thermal transfer printing should occur in the temperature range of 41° F to 95° F at 45% to 85% relative humidity. Suggested storage conditions for up to one year duration are 23° F to 104° F at 20% to 85% relative humidity. Exposing thermal transfer ribbons to direct sunlight or moisture will cause damage to the ribbons.



Ph: (800) 700-7377
Ph: (949) 888-3880
Fax: (949) 888-3883

ACCURATE IMAGING RESOURCES
22532 Avenida Empresa
Rancho Santa Margarita, CA 92688