



ULTRA PREMIUM WAX RESIN

Technical Specifications

Color Code Tab.....	Silver
Maximum Print Speed	8 IPS
Film Thickness.....	4.5 Microns
Total Ribbon Thickness...	7.5 Microns
Transmission Density	1.30
	MacBeth Scale
Ink Melting Point.....	81°C/178°F

UL Labeling Reference:
 Avery Fasson: UL MH 7834
 Flexoon: UL MH 16635

Premium Wax/Resin

Excellent Durability

Benefits

- Stands up to IPA, household cleaners and other mild chemicals
- Excellent scratch and smudge resistance
- Moderate level of steam resistance
- Well-suited for a variety of demanding labeling applications
- Backcoat protects printhead

Recommended Stock

Coated Paper Tag & Label Stocks
 Polyethylene Films

Polypropylene Films
 Polyester Films



What you need to know to quote ribbon business.

Thermal Transfer Ribbon STORAGE CONDITIONS
 For optimal print results, thermal transfer printing should occur in the temperature range of 41° F to 95° F at 45% to 85% relative humidity. Suggested storage conditions for up to one year duration are 23° F to 104° F at 20% to 85% relative humidity. Exposing thermal transfer ribbons to direct sunlight or moisture will cause damage to the ribbons.



Ph: (800) 700-7377
 Ph: (949) 888-3880
 Fax: (949) 888-3883

ACCURATE IMAGING RESOURCES
 22532 Avenida Empresa
 Rancho Santa Margarita, CA 92688